



GRIPPER FAST ADHESIVE

DUNLOP GRIPPER FAST is ideal for bonding carpet gripper, woods, metal trims, metal nosing, aluminium and many other types of products where a quick bond is required to concrete, timber and most other common building substrates. DUNLOP GRIPPER FAST has excellent resistance to high temperatures and water.



PREPARATION

All surfaces must be clean and sound, free of dust and any other contaminants that may affect bond.

APPLICATION

Apply thin bead of adhesive to one surface. Press the two surfaces to be bonded firmly together. Pressure may need to be applied to keep the two surfaces in contact while adhesive cures. Large extrusions should also be secured with appropriate fixing screws.

CURING TIME

Apply thin bead of adhesive to DUNLOP GRIPPER FAST is a moisture cure system. Allow approx. 1 hour curing time. This process may be accelerated by spraying a light mist of water to one of the surfaces. Thick beads will take longer to cure and will have a weaker bond than a thinner bead. The thicker the bead of DUNLOP GRIPPER FAST the more the product will tend to foam.

CLEAN UP

Remove any wet adhesive with suitable solvent cleaner before it cures. When cured remove by mechanical means.

SHELF LIFE

12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

SAFETY

This product may cause irritation and an allergic reaction to the skin. May cause serious eye and respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. Wear protective gloves, clothing, face, and eye protection. Avoid inhaling dust/fumes/gas/mist/vapours/spray. Ensure adequate ventilation during application. Check with your local Council regarding the disposal of contents, dispose of packaging thoughtfully and recycle where possible. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS). At times updates can occur to data, please ensure you have the most current Technical Data Sheets and SDS information found at dunlopbuildingproducts.com.

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

This datasheet was issued in September 2022 and is valid for 3 years, unless updated sooner. Always refer to www.dunlopbuildingproducts.com for the latest technical data from ARDEX Australia Pty Ltd.