

ROOF, GUTTER & POND



DUNLOP ROOF, GUTTER & POND is a highly flexible, silane modified adhesive and sealant. It is suitable for minor repairs, even those that need to be carried out underwater or whilst raining. DUNLOP ROOF, GUTTER & POND is grey in colour, can be painted over and is suitable for a wide range of applications to seal and repair joints and cracks.

SUBSTRATES

Concrete, wall panels, timber, waterproofing membranes, ceramic tiles, aluminium, plastic, metal, polystyrene foam, glass and glazed tiles.

SURFACE PREPARATION

In general, the substrate or joint must be clean, firm and free of dust, dirt, oil, grease, curing compounds, old adhesive residues, paints and coatings, bitumen, tar, release agents and other barrier materials. For optimum performance, the substrate or joint can be slightly damp.

APPLICATION

If in doubt about the suitability of the product for your project, carry out a trial application. Do not apply at temperatures below 5°C or above 35°C

As a sealant

1. Remove aluminium seal at the bottom of the cartridge, pierce the protective membrane at the tapered nozzle, attach and trim nozzle to required size and place cartridge in applicator gun.
2. Apply DUNLOP ROOF, GUTTER & POND onto substrate or over joint/crack and allow to cure.

As an adhesive

1. Remove aluminium seal at the bottom of the cartridge, pierce the protective membrane at the tapered nozzle, attach and trim nozzle to required size and place cartridge in applicator gun.
2. Apply DUNLOP ROOF, GUTTER & POND to the substrate or item to be fixed.
3. Press the items firmly together within 7-10 minutes (at a temperature of 23°C) and before skinning of the adhesive commences.
4. If using the product for spot fixing repairs, ensure that the maximum distance between the glue points is 25 to 30cm and observe the weight of the item being fixed.
5. Always remove a small layer of skinned adhesive before reusing

DRYING TIME

The drying time will depend on the substrate, climatic conditions and the materials being fixed or seal. Higher humidity will shorten the open time while lower humidity will extend the open time.

CLEAN UP

Any spillage can be removed when wet with a clean cloth.

SHELF LIFE

12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

STORAGE

Once finished using DUNLOP ROOF, GUTTER & POND close open cartridge and re-use as soon as possible. Note: Always remove a small layer of any skinned adhesive before reusing.

PRECAUTIONS

DUNLOP ROOF, GUTTER & POND achieves a good bond under water or when applied to a wet substrate. We recommend a trial application to ensure a good bond is achieved.

The long-term stability when fixed under water may vary depending on application. DUNLOP ROOF, GUTTER & POND can be over-painted after drying with most commonly used paints; due to the vast range of paints and coatings on the market we recommend a small test area prior to proceeding. Do not use DUNLOP ROOF, GUTTER & POND for chemical resistant applications.

Before any substrate preparation, installation or finishing methods relating to DUNLOP product are undertaken, please be aware of any potential risks and use appropriate PPE (personal protective equipment). This may involve contacting substrate manufacturers for Safety Data Sheets.

SAFETY DATA

This product may cause irritation and an allergic reaction to the skin. It may cause serious eye injury and irritation to the respiratory system. In case of contact with the eyes rinse with running water until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Wear protective gloves, clothing, eye and face protection. Avoid inhaling dust/fumes/gas/mist/vapours/spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Datasheet (SDS). At times updates can occur to data, please ensure you have the most current Technical Data Sheets and SDS information found at www.dunlopit.com.



ROOF, GUTTER & POND

10 YEAR GUARANTEE

Ardex Australia Pty Ltd ("we" or "us") guarantees this product (also referred to as "our goods") is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of application of the product if such application occurs within this product's specified shelf life. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or the cost of such replacement or repair, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow our published instructions or any act or circumstance beyond our control, including shade variations and efflorescence and faulty workmanship on the part of any installer or applicator of the product. If you wish to make a claim under this guarantee you must notify us (address: 7/20 Powers Road Seven Hills NSW 2147; phone: 1800222841; email: technicalservices@ardexaustralia.com), identify the product and provide evidence of your purchase and the subsequent application of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage and to undertake any inspections and tests necessary to establish your rights under this guarantee. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a "consumer" under the Australian Consumer Law and to that extent you need to be aware that: "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

This datasheet was issued in September 2020 and is valid for 3 years, unless updated sooner. Always refer to www.dunlopit.com for the latest technical data from ARDEX Australia Pty. Ltd.