



DUNLOP SUPER *Lite* TILE ADHESIVE



DUNLOP SUPERLITE TILE ADHESIVE is a high bond, lightweight mastic type wall and floor tile adhesive suitable for most tiling applications. The lightweight adhesive is easy to pick up and transport and is easy to spread with the trowel. This environmentally sustainable formula is sand free with reduced dust during mixing. Ideal for use over many surfaces as well as most tile types including large format tiles in residential and commercial areas. Suitable for both indoor and outdoor use, DUNLOP SUPERLITE can even be used for swimming pools.

SUITABLE SURFACES

Suitable for use over concrete, render, screeds, fibre-cement sheet, plasterboard walls, compressed fibre-cement sheet floors, Dunlop Waterproofing Membranes, existing ceramic tiles (indoors, dry areas) and ceramic tile underlay over timber.

TILE TYPES

Ceramic, porcelain, natural stone (excluding moisture sensitive stone) mosaics and fully vitrified tiles.

COLOUR

White

CLASSIFICATION

C2 TE S1

SURFACE PREPARATION

Surfaces must be consistently flat and firmly fixed. Clean off dust, oil, grease and all loose contaminating materials. Ensure surfaces are dry before tiling, with no residue or permanent damp and ensure the surface is strong enough to support the weight of the tiles being fixed. Prime porous surfaces with DUNLOP PRIMER & ADDITIVE or DUNLOP MULTIPURPOSE PRIMER. Before fixing tiles, ensure the surface's drying time has elapsed.

CONCRETE

Early age concrete must be at least 7 days old and no less than 20MPa. The surface should be true and level and pitched to drains where required. Remove any concrete sealers or curing compounds from the surface, e.g. chlorinated rubber, resin, wax sealers. Steel trowel finished concrete or smooth/dense concrete greater than 35MPa should be roughened mechanically to remove laitance and provide a good key for tiling.

FIBRE-CEMENT SHEET (WALLS), PLASTERBOARD AND COMPRESSED FIBRE-CEMENT SHEET FLOORS

Fix sheets according to manufacturer's instructions, ensuring that they are suitable for tiling over. Priming with DUNLOP PRIMER & ADDITIVE or DUNLOP MULTIPURPOSE PRIMER is recommended for fibre-cement sheets. Refer to manufacturers' installation guide for jointing compressed fibre-cement sheets. Tiling over compressed fibre-cement sheet for outdoor applications should be carried out as per the Australian standard AS 3958 and sheet manufacturer's instructions.

CEMENT RENDER WALLS & SCREDED FLOORS

New renders and screeds should be finished with a wood float to the required surface regularity. Screeds should be pitched to drains where required. For bonded screeds allow 24 hours to

cure prior to tiling. For unbonded screeds allow at least 7 days to cure prior to tiling. Prime with DUNLOP PRIMER & ADDITIVE or DUNLOP MULTIPURPOSE PRIMER and allow to dry.

CERAMIC TILE UNDERLAY (CTU) OVER ENGINEERED SHEET TIMBER FLOORS

Fix CTU as per the manufacturer's instructions. The CTU must be at least 6mm thick and made specifically for this purpose. Tiles under 100mm edge length cannot be fixed over CTU with DUNLOP SUPERLITE TILE ADHESIVE.

EXISTING CERAMIC TILES (INDOOR DRY AREA ONLY)

The existing tiles must be firm and stable. Roughen the surface of existing tiles by mechanical means and clean off contamination and dust before tiling. Ensure that at least 80% of the glaze is removed. Alternatively use DUNLOP BONDCOAT as per the datasheet for the BONDCOAT. This adhesive is not suitable for tiling over existing tiles in immersed applications, use DUNLOP TILE-ALL for this application.

DUNLOP WATERPROOFING MEMBRANES

Dunlop Waterproofing Membranes must be applied according to instructions and thoroughly dry prior to tiling.

MIXING

1. Use 5.5L of water for a 11kg bag. The consistency of the adhesive can be slightly adjusted to suit site conditions and size, weight and type of tiles and location the tiles are to be fixed.
2. Add DUNLOP SUPERLITE TILE ADHESIVE powder to clean water in a clean container and mix to a creamy consistency for 2 minutes.
3. Allow to stand for 2 minutes re-stir the mixture thoroughly for another 2 minutes and the adhesive is ready for use.
4. Re-stir the mixture thoroughly and the adhesive is ready for use for up to 90 minutes at 23°C and 50% relative humidity.
5. Do not apply at temperatures below 10°C or above 35°C.

APPLICATION RANGE

- Tiling practices must be in accordance with AS 3958. Ensure the surface has been prepared and the tiles are free from dust. Use the appropriate notched trowel to achieve 100% coverage, this will depend on the surface, type and size of tile. As a general guide, use a 6 x 6 x 6mm trowel on walls, 10 x 10 x 10mm trowel on floors. Do not apply adhesive at a bed thickness greater than 10mm or less than 3mm.
- Spread approximately one square metre at a time ensuring that a skin has not developed prior to bedding the tiles (this adhesive has an open time of 30 minutes before skinning occurs depending on site conditions and has an adjustment time of 20 minutes).



DUNLOP SUPER *Lite* TILE ADHESIVE



- Press and slide the tile at right angles to the notch pattern to ensure 100% coverage on the back of the tile.
- Deeply keyed quarry tiles and tiles greater than 400mm on an edge, do require buttering of the adhesive on the back of the tiles to ensure complete coverage.
- Lift a tile from time to time to check that there are no voids beneath the tile. Do not spot fix tiles.
- Any surplus adhesive must be removed from the surface of the tile and joints, before the adhesive sets.
- Allow adhesive to set firm (24 hours) before grouting and allowing foot traffic, depending on temperature and surface porosity.

DRYING TIMES & GROUTING

Approximately 24 hours, at 23°C and 50% relative humidity. Allow longer for dense tiles/substrates, humid climates and low temperatures. Use DUNLOP COLOURED GROUT for flexible and mould resistant joints. For joints greater than 8mm, use DUNLOP WIDE JOINT GROUT. To enhance the colour of the grout, impart a degree of flexibility and reduce porosity and staining, use in conjunction with DUNLOP PRIMER & ADDITIVE.

MOVEMENT JOINTS

Movement joints must be in accordance with AS3958. As a general guide, movement joints should be incorporated at 3–5 metre intervals and around the perimeter of the floor. Any structural movement joints and penetrations must be carried through to the face of the tiling. These joints and penetrations must be approximately 6mm wide and kept free from adhesive and grout droppings. They shall be filled with a suitable flexible material such as DUNLOP COLOURED SILICONE or a proprietary joint system. For walls, incorporate movement joints at internal corners, fixtures interrupting the tile surface, at 3.5 metre intervals and storey height for external fixing.

COVERAGE

11kg of DUNLOP SUPERLITE TILE ADHESIVE is sufficient for approximately 10.5m² on walls, using a 6 x 6 x 6mm notched trowel and 7m² on floors using a 10 x 10 x 10mm notched trowel. The coverage will vary depending on substrate condition, tile type and application technique.

CLEAN UP

Clean tools in water immediately after use.

SHELF LIFE

12 months when stored in the original unopened packaging, in a dry place at 23°C and 50% relative humidity.

PRECAUTIONS

- Not suitable for use over floors with a deflection greater than the joist span divided by 500 for tiles less than 600mm and divided by 720 for greater sized tiles. Joint span must comply with AS 1684.
- Do not use this adhesive to fix moisture sensitive natural stone (e.g. green marble).

- Do not use this adhesive over timber, metal or surfaces subject to shrinkage or movement.

SAFETY DATA

This product may cause irritation and an allergic reaction to the skin. It may cause serious eye injury and irritation to the respiratory system. In case of contact with the eyes rinse with running water until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Wear protective gloves, clothing, eye and face protection. Avoid inhaling dust/fumes/gas/mist/vapours/spray. Ensure adequate ventilation during mixing and application. Store locked up. Check with your local Council regarding the disposal of contents, dispose of packaging thoughtfully and recycle where possible. Keep out of the reach of children. Call the Poisons Information Centre on 131 126 (AUS) and 0800 764 766 (NZ) or call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS) at www.dunlopit.com. Additional information is in the Safety Data Sheet (SDS) at www.dunlopit.com.

CONTAINS

PORTLAND CEMENT, 65997-15-1, >40%, GLASS, OXIDE, 65997-17-3 10-40%, PERLITE, 93763-70-3, <5%

10 YEAR GUARANTEE

Ardex Australia Pty Ltd (“we” or “us”) guarantees this product (also referred to as “our goods”) is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of application of the product if such application occurs within this product’s specified shelf life. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or the cost of such replacement or repair, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow our published instructions or any act or circumstance beyond our control, including shade variations and efflorescence and faulty workmanship on the part of any installer or applicator of the product. If you wish to make a claim under this guarantee you must notify us (address: 7/20 Powers Road Seven Hills NSW 2147; phone: 1800222841; email: technicalservices@ardexaustralia.com), identify the product and provide evidence of your purchase and the subsequent application of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage and to undertake any inspections and tests necessary to establish your rights under this guarantee. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a “consumer” under the Australian Consumer Law and to that extent you need to be aware that: “Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss of damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure”.

This datasheet was issued in July 2021 and is valid for 3 years, unless updated sooner. Always refer to www.dunlopit.com.au for the latest technical data from ARDEX Australia Pty Ltd.