



# TIMBER JOINT SEALANT

**DUNLOP TIMBER JOINT SEALANT** is an acrylic sealant for use in joints such as wall and floor joints, for laminate, parquet and wooden floorboards. It has great adhesion and can be sanded and painted over to complete finishing. Suitable for indoor use, this solvent-free formula is the ideal solution for sealing all movement joints up to 30mm. Do not use under waterproofing membranes or in continuous immersion applications.

## PRODUCT ATTRIBUTES

**Product colours:** Beech, Grey Oak

**Composition:** Paste

**Size:** 310mL

## APPLICATION

Apply at temperatures between 5°C and 35°C.

1. Ensure joints and surfaces are dry, clean and free from grease, soap and water.
2. Maximum joint width is 30mm and depth 15mm. For joints greater than 10mm deep a backing rod should be used. To achieve a neater finish mask joint edges with tape.
3. Trim nozzle end to obtain correct bead width and place cartridge in applicator gun.
4. Apply sealant in a steady continuous bead ensuring good contact with both sides of the joint. Tool off with DUNLOP Smoothing Tool and moisten with a solution of detergent and water to finish the joint smoothly before a skin forms (10 mins).
5. While the sealant is still wet, clean off any excess. If joint edges have been masked, remove tape whilst still wet. If the sealant has dried on the surface, clean with white spirit solvent to soften the sealant then scrape off with a blade.
6. Allow 3 days to cure before sanding.

## SHELF LIFE

12 months when stored in original unopened packaging in a dry place at 23°C and 50% relative humidity.

## PRECAUTIONS

Contact with natural stone, bitumen-based materials and rubber modified adhesives and metals such as brass and copper, may cause discolouration. Not suitable for use in continuous immersion situations.

Before any substrate preparation, installation or finishing methods relating to DUNLOP products are undertaken, please be aware of any potential risks and use appropriate PPE (personal protective equipment). This may involve contacting substrate manufacturers for Safety Data Sheets.

## SAFETY DATA

This product may cause an allergic skin reaction. Avoid contact with skin and eyes, in case of contact with the eyes, wash out immediately with fresh running water. If irritation continues, seek medical attention. Wear protective gloves, clothing, face and eye protection. Avoid inhaling fumes/vapours. Ensure adequate ventilation during mixing and application. Check with your local Council regarding disposal of contents, dispose

of packaging thoughtfully and recycle where possible. Keep out of the reach of children. Call a doctor if you feel unwell. Additional information is in the Safety Data Sheet (SDS) and review the latest Technical Datasheet at [dunloptrade.com.au](http://dunloptrade.com.au)

## DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for the uses they are intended. Users are advised to confirm that this product is suitable for their application and conforms with the specifications of the system being employed and other products in that system. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may affect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

This datasheet was issued in February 2025 and is valid for 3 years, unless updated sooner. Always refer to [dunloptrade.com.au](http://dunloptrade.com.au) for the latest technical data from ARDEX Australia Pty Ltd.

### ARDEX Australia Pty Ltd

2 Buda Way, Kemps Creek NSW 2178

Phone: 1300 788 780 | Technical Support: 1800 222 841  
[technicalservices@ardexaustralia.com](mailto:technicalservices@ardexaustralia.com)

### ARDEX New Zealand Ltd

15 Alfred Street, Onehunga, Auckland 1061

Phone: 0800 227 339 | Technical Support: 0800 224 070  
[info@ardexnz.com](mailto:info@ardexnz.com)