

# How-to APPLY SILICONE

## DUNLOP COLOURED SILICONE

- > Flexible sealant for use in joints such as wall and floor joints, tiled surfaces and bench tops, bath edges, cupboards, splashbacks and movement joints.
- > Adheres to ceramic tiles, glass, enamel, aluminium, granite, porcelain and sanitary acrylics.
- > Suitable for indoor and outdoor use, DUNLOP COLOURED SILICONE is waterproof, contains a fungicide to fight mould and is suitable for use in showers.



## APPLICATION

### STEP 1

Ensure joints and surfaces are dry, clean and free from grease, soap and water.

### STEP 2

Trim end nozzle to obtain correct bead width and place cartridge applicator in caulking gun.

### STEP 3

Apply sealant in a steady continuous bead ensuring good contact with both sides of the joint. Tool off with a moistened spatula to finish the joint smoothly before a skin forms.

### STEP 4

If the silicone has dried on the surface, clean with white spirit solvent or turpentine to soften the silicone then scrape off with a blade.

## HANDY HINT

- > Select a DUNLOP COLOURED SILICONE that matches your DUNLOP COLOURED GROUT and complements your tiles.

## Toll Free Hotline

1800 222 841 (AU)

0800 224 070 (NZ)

[www.dunlopdiiy.com](http://www.dunlopdiiy.com)



### Want more info?

Use the QR reader on your smartphone to view DIY video.

ARDEX Australia Pty Ltd  
1300 788 780 (AU)



9 315021 022575 >

 **DUNLOP**